

Four-Faith

8-port Gigabit rugged Industrial Switch

FNS100-08-AGB-M12-A-IP65

Introduction

FNS100-08-AGB-M12-A-IP65 is a rugged Industrial switch with M12 connector, it is specially used in Vehicles, airlines, automation Industry etc. which requires to experience vibration and shocks. The switch meets CE, FCC, Rohs standard, IP65 protection, with working temperature from - 40℃ to 75℃ . it provides to user more safety, reliable solution on vehicles.

Features

- M12 interface, gigabit port is M12 X-coded type
- Wall-mounted installation
- Support full duplex or half duplex mode, and with automatic negotiation capability
- The network port supports automatic cross recognition

  Store and forward, support a variety of protocols
- In line with industrial operating standards, the average trouble-free work is more than 300,000 hours
- Power supply: Non-PoE type DC 12-52V
- Power Socket: M12(Male), 5-Pin A coded

8-port Gigabit rugged Industrial Switch
FNS100-08-AGB-M12-A-IP65


Production Specification

Model No.	**FNS100-08-AGB-M12-A-IP65**
Description	8-port Gigabit rugged Industrial Switch
Ethernet Port	8 port M12 X-coded 8-pin(F)
Power Connector	M12 A-coded 5-pin(F)
Performance Specification	Bandwidth: 20Gbps Packet Buffer Memory:2Mbit Packet Forwarding Rate:15Mpps MAC Address Table: 8K
Installation	Wall mounted
Flow Control	Back pressure for half duplex, IEEE 802.3x pause frame for full duplex
Enclosure	IP65 aluminum housing
LED Indicator	Power: PWR Ethernet: Green(Link/Act)
Power Input	12 to 52V DC input
Power Consumption	<10 watts
Network Protocols	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u;100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x;
Network cables	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤10meter) 1000BASE-TX: Cat6 or later UTP(≤100 meter)

8-port Gigabit rugged Industrial Switch
FNS100-08-AGB-M12-A-IP65

Industry Standard	EMI：FCC Part 15，CISPR (EN55032) class A EMS: EN61000-4-2 (ESD)，Level 3 EN61000-4-3 (RS)，Level 3 EN61000-4-4 (EFT)，Level 3 EN61000-4-5 (Surge)，Level 3 EN61000-4-6 (CS)，Level 3 EN61000-4-8，Level 4 Impact: IEC60068-2-27 Free fall：IEC 60068-2-32 Shock：IEC60068-2-6
Dimensions (W x D x H)	186*150*50mm
Weight	Product Weight: 0.65KG Packing Weight: 0.75KG
Working Environment	Working temperature: -40～75℃ ; Storage temperature: -40～85℃ Relative Humidity: 5%~95 %(no condensation)

Dimensions



8-port Gigabit rugged Industrial Switch
FNS100-08-AGB-M12-A-IP65

Order Information

Model	Description
FNS100-08-AGB-M12-A-IP65	8-port Gigabit rugged Industrial Switch, IP65