
Unmanaged Industrial Switch

FNS100-28-AGB-S



Din-Rail

Terminal Block

Introduction

FNS100-28-AGB-S is a network unmanaged industrial Ethernet switch, complies with FCC, CE, RoHS standards. Support 2 Gigabit optical ports and 8 Gigabit electrical ports; this series of switches adopts low power consumption and fanless design to ensure no noise interference; At the same time, it supports -40~70°C working temperature and good EMC electromagnetic compatibility performance, ensuring stable work in harsh industrial environments, and building fast and stable network terminal interfaces for industrial applications such as factory automation, intelligent transportation, and video surveillance. Provide a safe and reliable solution for accessing the network.

Industrial-grade Design

- Metal casing, IP40 protection level
- Wide range operating temperature (-40ºC~70ºC)

Stability & Reliability

- Support low power consumption, fanless and silent design, metal shell, excellent on heat dissipation, stable quality

Standard & Convenience

- Support plug and play, flexible networking
- Support DIN-Rail and wall mounting
- Support POE (Optional)


Four-Faith

Tel: 400-8838-199

Web: www.fourfaith.com

V2.0.0 Copyright @ Four-Faith 2023

Unmanaged Industrial Switch FNS100-28-AGB-S




Production Specification

Standard	
Model	FNS100-AGB-S
Item	**Content**
Ethernet Standard	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u;100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x,IEEE 802.3af,IEEE 802.3at;and,etc.
Industry Standard	EMI：FCC Part 15 Subpart B Class A，EN 55022 Class A EMC: IEC(EN)61000-4-2(ESD): ±6kV Contact discharge, ±8kV Air discharge IEC(EN)61000-4-3(RS) : 10V/m(80 ~ 1000MHz) IEC(EN)61000-4-4(EFT): ethernet port: ±2kV CM//±1kV DM. IEC(EN)61000-4-5(Surge): ethernet port: ±2kV CM//±1kV DM. IEC(EN)61000-4-6(Radio frequency conduction) : 3V(10kHz ~ 150kHz),10V(150kHz ~ 80MHz) IEC(EN)61000-4-16(Common mode conduction): 30V cont. 300V,1s IEC (EN)61000-4-8 Shock：IEC 60068-2-27 Freefall：IEC 60068-2-32 Vibration：IEC 60068-2-6

Switching Characteristics	
Model	FNS100-AGB-S
Item	**Content**
Buffer Memory	2Mbit
Transmission Method	Store-and-forward
Backplane Bandwidth	20G
Switching Latency	<10μs
MAC Address	4K
Power	
Item	**Content**
Input Voltage	Non POE：DC12-52V POE：DC48-57V (Dual power redundancy backup)
Access Terminal	Phoenix terminal block

V2.0.0 Copyright @ Four-Faith 2023

Unmanaged Industrial Switch FNS100-28-AGB-S



Characteristics	Support dual power supply redundancy Support built-in over-current protection Support reverse connection protection with 4.0 A

Operating Environment	
Item	**Content**
Operating Temperature	-40 ºC ~70ºC
Storage Temperature	-40 ºC ~85ºC
Relative Humidity	5~95% (Non-condensing))

POE Standard（Optional）	
Item	**Content**
PoE Standard	IEEE802.3af/ IEEE802.3at
PoE Port	1-8 port support PoE
Output Power	Single port maximum power 15.4 W (IEEE 802.3 af) 30 W (IEEE 802.3 at)

Interfaces	
Item	**Content**
SFP Slot	Number：2 Type：1000BaseFX port (SFP slot), supporting 100 megabytes
Ethernet Port	Number：8 Type：RJ45, 10/100/1000M automatic detection, full/half duplex MDI/MDI-X adaptive
Optical Fiber	Support single-mode/multi-mode fiber Multi-mode fiber: 550M Single-mode optical fiber: 20/40/60/80/100KM


Other	
Model	**FNS100-AGB-S**
Item	**Content**
Shell	IP40 protection level, metal casing
Characteristic	Support plug and play, flexible networking
Dimension	142.5×103.5×47.5mm
Weight	0.64Kg
Installation Method	DIN rail and wall mounted
Heat-dissipating Method	Natural cooling, no fan
LED	Power Indicator: PWR Port indicator: POE port, SFP port (Link/ACT)

V2.0.0 Copyright @ Four-Faith 2023

Unmanaged Industrial Switch FNS100-28-AGB-S



Dimension (mm): 142.5×103.5×47.5mm



Order Information

Model	Description
FNS100-28-AGB-S	Unmanaged Industrial Switch: 2 Gigabit optical port + 8-Port RJ45, DC12~48V input, wide temperature (-40 ° C -70 ° C), DC 12V/1A power adapter

Four-Faith 四信®

V2.0.0 Copyright @ Four-Faith 2023