

CV200XEU/XNA
Additional Camera Accessories

CV200XEU/XNA can connect a secondary camera to meet more diversified application needs such as the monitoring of cargo or cabin view and driver behavior.

DMS Camera

ADSM001

Monitor the driver states to avoid dangerous driving behaviors by vision algorithm



Dimension	50(W) x 77(L) x 124(H) mm
Cable	Length: 0.57 meters Connector: 4 PIN BM port
FOV	D=62° H=50° V=32°
Camera Resolution	1280P x 720P
IR LED	LED (940nm)/1m
Video Signal	AHD
Operating Temperature	-20℃ ~ +60℃
Installation	Dashboard mount, 3M adhesive tape or screw

Interior Camera

ACAM001

Monitor the cabin or cargo



Dimension	30(W) x 70(L) x 37(H) mm
Cable	Length: 0.57 meters Connector: 4 PIN BM port
FOV	D=136° H=110° V=58°
Camera Resolution	1280P x 720P
IR LED	LED (940nm)/5m
Video Signal	AHD
Operating Temperature	-20℃ ~ +70℃
Installation	Front windshield mount, 3M adhesive tape

Windshield Rear View Camera

ACAM002

Monitor the rear view



Dimension	33(W) x 73(L) x 30(H) mm
Cable	Length: 0.5 meters Connector: 4 PIN BM port
FOV	D=131° H=111° V=59°
Camera Resolution	1280P x 720P
IR LED	Full Day Color
Video Signal	AHD
Operating Temperature	-20℃ ~ +70℃
Installation	Rear windshield mount, 3M adhesive tape

Water Resistant Cargo View Dome Camera

ACAM120

Monitor the cargo



Dimension	68(H) x 93.2(D) mm
Cable	Length: 0.57 meters Connector: aviation port
FOV	D=108° H=90° V=48°
Camera Resolution	1280P x 720P
IR LED	LED (850nm)/10m
Video Signal	AHD
Operating Temperature	-20℃ ~ +70℃
IP Rating	IP65
Installation	Ceiling mount, screw

Waterproof Rear View Square Camera

ACAM130

Monitor the rear view



Dimension	68(W) x 81(L) x 68.5(H) mm
Cable	Length: 0.57 meters Connector: aviation port
FOV	D=131° H=111° V=59.6°
Camera Resolution	1280P x 720P
IR LED	LED (850nm)/10m
Video Signal	AHD
Operating Temperature	-20℃ ~ +70℃
IP Rating	IP69
Installation	Load bay mount, screw