# CV200XEU/XNA
# Additional Camera Accessories

CV200XEU/XNA can connect a secondary camera to meet more diversified application needs such as the monitoring of cargo or cabin view and driver behavior.

## DMS Camera

### ADSM001

Monitor the driver states to avoid dangerous driving behaviors by vision algorithm



| | |
|---|---|
| Dimension | 50(W) x 77(L) x 124(H) mm |
| Cable | Length: 0.57 meters<br>Connector: 4 PIN BM port |
| FOV | D=62° H=50° V=32° |
| Camera Resolution | 1280P x 720P |
| IR LED | LED (940nm)/1m |
| Video Signal | AHD |
| Operating Temperature | -20℃ ~ +60℃ |
| Installation | Dashboard mount, 3M adhesive tape or screw |

## Interior Camera

### ACAM001

Monitor the cabin or cargo



| | |
|---|---|
| Dimension | 30(W) x 70(L) x 37(H) mm |
| Cable | Length: 0.57 meters<br>Connector: 4 PIN BM port |
| FOV | D=136° H=110° V=58° |
| Camera Resolution | 1280P x 720P |
| IR LED | LED (940nm)/5m |
| Video Signal | AHD |
| Operating Temperature | -20℃ ~ +70℃ |
| Installation | Front windshield mount, 3M adhesive tape |

## Windshield Rear View Camera

### ACAM002

Monitor the rear view



| | |
|---|---|
| Dimension | 33(W) x 73(L) x 30(H) mm |
| Cable | Length: 0.5 meters<br>Connector: 4 PIN BM port |
| FOV | D=131° H=111° V=59° |
| Camera Resolution | 1280P x 720P |
| IR LED | Full Day Color |
| Video Signal | AHD |
| Operating Temperature | -20℃ ~ +70℃ |
| Installation | Rear windshield mount, 3M adhesive tape |

## Water Resistant Cargo View Dome Camera

### ACAM120

Monitor the cargo



| | |
|---|---|
| Dimension | 68(H) x 93.2(D) mm |
| Cable | Length: 0.57 meters<br>Connector: aviation port |
| FOV | D=108° H=90° V=48° |
| Camera Resolution | 1280P x 720P |
| IR LED | LED (850nm)/10m |
| Video Signal | AHD |
| Operating Temperature | -20℃ ~ +70℃ |
| IP Rating | IP65 |
| Installation | Ceiling mount, screw |

## Waterproof Rear View Square Camera

### ACAM130

Monitor the rear view



| | |
|---|---|
| Dimension | 68(W) x 81(L) x 68.5(H) mm |
| Cable | Length: 0.57 meters<br>Connector: aviation port |
| FOV | D=131° H=111° V=59.6° |
| Camera Resolution | 1280P x 720P |
| IR LED | LED (850nm)/10m |
| Video Signal | AHD |
| Operating Temperature | -20℃ ~ +70℃ |
| IP Rating | IP69 |
| Installation | Load bay mount, screw |